

# Safety Data Sheet

## according to WHS Regulations

Printing date 10.03.2017

Version number 166


Revision: 10.03.2017

Hazardous according to criteria of Australian Safety and Compensation Council.

### 1 Identification

- **Product identifier**
- **Trade name:** Sure Lift with Dye J6D
- **Article number:** 69231AU
- **Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- **Application of the substance / the mixture**
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Dayton Superior Corporation (Australia) PTY LTD  
5A Connection Drive  
Campbellfield, VIC 3061  
Australia  
Australia Phone: +61 1300 DAYTON (329866)
- **Emergency telephone number:**  
Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call international number, +1 703 741-5970. Collect calls are accepted.  
Australia in-country +61-290372994

### 2 Hazard(s) Identification

- **Classification of the substance or mixture**  
Flam. Liq. 3 H226 Flammable liquid and vapour.  
Eye Dam. 1 H318 Causes serious eye damage.  
Muta. 1A H340 May cause genetic defects.  
Carc. 1A H350 May cause cancer.  
STOT RE 1 H372 Causes damage to the central nervous system through prolonged or repeated exposure.  
Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.
- **Label elements**
- **GHS label elements** The product is classified and labelled according to the Globally Harmonised System (GHS).
- **Hazard pictograms**  


GHS02   GHS05   GHS08
- **Signal word** Danger
- **Hazard-determining components of labelling:**  
Stoddard solvent  
1,2,4-trimethylbenzene  
Naphtha (petroleum), hydrodesulfurized heavy  
Solvent naphtha (petroleum), light arom.
- **Hazard statements**  
Flammable liquid and vapour.  
Causes serious eye damage.  
May cause genetic defects.  
May cause cancer.

(Contd. on page 2)

# Safety Data Sheet

## according to WHS Regulations

Printing date 10.03.2017

Version number 166

Revision: 10.03.2017

**Trade name: Sure Lift with Dye J6D**

(Contd. of page 1)

Causes damage to the central nervous system through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

· **Precautionary statements**

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

### 3 Composition and Information on Ingredients

· **Chemical characterisation: Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

8052-41-3	Stoddard solvent ⚠ Flam. Liq. 3, H226; ⚠ Muta. 1B, H340; Carc. 1B, H350; STOT RE 1, H372; Asp. Tox. 1, H304	25-50%
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy ⚠ Flam. Liq. 3, H226; ⚠ Muta. 1B, H340; Carc. 1B, H350; STOT RE 1, H372; Asp. Tox. 1, H304	25-50%
64742-95-6	Solvent naphtha (petroleum), light arom. ⚠ Flam. Liq. 3, H226; ⚠ Muta. 1B, H340; Carc. 1B, H350; Asp. Tox. 1, H304	≤ 10%
95-63-6	1,2,4-trimethylbenzene ⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	≤ 10%
78-83-1	butanol ⚠ Flam. Liq. 3, H226; ⚠ Eye Dam. 1, H318; ⚠ Skin Irrit. 2, H315; STOT SE 3, H335-H336	≤ 5%
64742-47-8	Distillates (petroleum), hydrotreated light ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304	≤ 2.5%
98-82-8	cumene ⚠ Flam. Liq. 3, H226; ⚠ Carc. 2, H351; Asp. Tox. 1, H304; ⚠ STOT SE 3, H335	≤ 2.5%
64742-48-9	Naphtha (petroleum), hydrotreated heavy ⚠ Muta. 1A, H340; Carc. 1A, H350; Asp. Tox. 1, H304; Flam. Liq. 4, H227	≤ 1%
91-20-3	naphthalene ⚠ Carc. 2, H351; ⚠ Acute Tox. 4, H302; Flam. Liq. 4, H227	≤ 1%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

### 4 First Aid Measures

· **Description of first aid measures**

· **General information:** Immediately remove any clothing soiled by the product.

· **After inhalation:**

Immediately move exposed person to fresh air. If breathing difficulty persists or develops get prompt medical attention.

(Contd. on page 3)

## Safety Data Sheet according to WHS Regulations

Printing date 10.03.2017

Version number 166

Revision: 10.03.2017

**Trade name: Sure Lift with Dye J6D**

(Contd. of page 2)

- **After skin contact:**  
Immediately wash with water and soap and rinse thoroughly.  
If skin irritation continues, consult a doctor.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Seek medical treatment.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

### 5 Fire Fighting Measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Foam
- **For safety reasons unsuitable extinguishing agents:** Water
- **Special hazards arising from the substance or mixture** Formation of toxic gases is possible during heating or in case of fire.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

### 6 Accidental Release Measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### 7 Handling and Storage

- **Handling:**
- **Precautions for safe handling**  
Wear appropriate personal protective clothing to prevent eye and skin contact. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Do not take internally.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:** cool and dry
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.

(Contd. on page 4)

# Safety Data Sheet

## according to WHS Regulations

Printing date 10.03.2017

Version number 166

Revision: 10.03.2017

Trade name: Sure Lift with Dye J6D

(Contd. of page 3)

· **Specific end use(s)** No further relevant information available.

### 8 Exposure controls and personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.

· **Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

#### 8052-41-3 Stoddard solvent

WES (Australia) Long-term value: 790 mg/m<sup>3</sup>

#### 78-83-1 butanol

WES (Australia) Long-term value: 152 mg/m<sup>3</sup>, 50 ppm

#### 98-82-8 cumene

WES (Australia) Short-term value: 375 mg/m<sup>3</sup>, 75 ppm  
Long-term value: 125 mg/m<sup>3</sup>, 25 ppm  
Sk

#### 91-20-3 naphthalene

WES (Australia) Short-term value: 79 mg/m<sup>3</sup>, 15 ppm  
Long-term value: 52 mg/m<sup>3</sup>, 10 ppm

· **Additional information:** The lists valid during the making were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Eye protection:** Wear appropriate eye protection to prevent eye contact.

### 9 Physical and Chemical Properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

**Form:** Liquid

**Colour:** According to product specification

· **Odour:** Characteristic

(Contd. on page 5)

## Safety Data Sheet according to WHS Regulations

Printing date 10.03.2017

Version number 166

Revision: 10.03.2017

Trade name: Sure Lift with Dye J6D

(Contd. of page 4)

· <b>Odour threshold:</b>	Not determined.
· <b>pH-value:</b>	Not determined.
· <b>Change in condition</b> <b>Melting point/freezing point:</b>	Undetermined.
<b>Initial boiling point and boiling range:</b>	162 °C
· <b>Flash point:</b>	40 °C
· <b>Flammability (solid, gas):</b>	Not applicable.
· <b>Ignition temperature:</b>	230 °C
· <b>Decomposition temperature:</b>	Not determined.
· <b>Auto-ignition temperature:</b>	Product is not selfigniting.
· <b>Explosive properties:</b>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· <b>Explosion limits:</b>	
<b>Lower:</b>	1.1 Vol %
<b>Upper:</b>	6.0 Vol %
· <b>Vapour pressure at 20 °C:</b>	1 hPa
· <b>Density at 20 °C:</b>	0.77 g/cm <sup>3</sup>
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient: n-octanol/water:</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic at 20 °C:</b>	0 mPas
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	21.6 %
<b>Solids content:</b>	15.0 %
· <b>Other information</b>	No further relevant information available.

### 10 Stability and Reactivity

- **Reactivity** No decomposition if stored and applied as directed.
- **Chemical stability** No decomposition if stored and applied as directed
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

AU

(Contd. on page 6)

# Safety Data Sheet

## according to WHS Regulations

Printing date 10.03.2017

Version number 166

Revision: 10.03.2017

Trade name: Sure Lift with Dye J6D

(Contd. of page 5)

### 11 Toxicological Information

- **Information on toxicological effects**
- **Acute toxicity**

- **LD/LC50 values relevant for classification:**

**64742-95-6 Solvent naphtha (petroleum), light arom.**

Oral	LD50	>6800 mg/kg (rat)
------	------	-------------------

Dermal	LD50	>3400 mg/kg (rab)
--------	------	-------------------

Inhalative	LC50/4 h	>10.2 mg/l (rat)
------------	----------	------------------

**95-63-6 1,2,4-trimethylbenzene**

Oral	LD50	5000 mg/kg (rat)
------	------	------------------

- **Primary irritant effect:**
- **Skin corrosion/irritation** May cause skin irritation.
- **Serious eye damage/irritation** Irritating effect.
- **Respiratory or skin sensitisation** No sensitising effects known.
- **Additional toxicological information:**  
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:  
Irritant  
Carcinogenic.

### 12 Ecological Information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**  
Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water  
Do not allow product to reach ground water, water course or sewage system, even in small quantities.  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water  
Harmful to aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 7)

# Safety Data Sheet

## according to WHS Regulations

Printing date 10.03.2017

Version number 166

Revision: 10.03.2017


Trade name: Sure Lift with Dye J6D

(Contd. of page 6)

It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state, federal, and provincial environmental regulations.

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

<ul style="list-style-type: none"> <li>· UN-Number</li> <li>· ADG, IMDG, IATA</li> </ul>	UN1268
<ul style="list-style-type: none"> <li>· UN proper shipping name</li> <li>· ADG</li> <li>· IMDG, IATA</li> </ul>	1268 PETROLEUM DISTILLATES, N.O.S. PETROLEUM DISTILLATES, N.O.S.
<ul style="list-style-type: none"> <li>· Transport hazard class(es)</li> <li>· ADG, IMDG, IATA</li> </ul>	<div style="text-align: center;">  </div>
<ul style="list-style-type: none"> <li>· Class</li> <li>· Label</li> </ul>	3 Flammable liquids. 3
<ul style="list-style-type: none"> <li>· Packing group</li> <li>· ADG, IMDG, IATA</li> </ul>	III
<ul style="list-style-type: none"> <li>· Environmental hazards:</li> <li>· Marine pollutant:</li> </ul>	No
<ul style="list-style-type: none"> <li>· Special precautions for user</li> <li>· Danger code (Kemler):</li> <li>· EMS Number:</li> </ul>	Warning: Flammable liquids. 30 F-E,S-E
<ul style="list-style-type: none"> <li>· Transport in bulk according to Annex II of Marpol and the IBC Code</li> </ul>	Not applicable.
<ul style="list-style-type: none"> <li>· Transport/Additional information:</li> </ul>	
<ul style="list-style-type: none"> <li>· ADG</li> <li>· Limited quantities (LQ)</li> <li>· Excepted quantities (EQ)</li> </ul>	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
<ul style="list-style-type: none"> <li>· Transport category</li> <li>· Tunnel restriction code</li> </ul>	3 D/E
<ul style="list-style-type: none"> <li>· IMDG</li> <li>· Limited quantities (LQ)</li> <li>· Excepted quantities (EQ)</li> </ul>	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 8)



# Safety Data Sheet

## according to WHS Regulations

Printing date 10.03.2017

Version number 166

Revision: 10.03.2017

Trade name: *Sure Lift with Dye J6D*

(Contd. of page 7)

· UN "Model Regulation":

UN 1268 PETROLEUM DISTILLATES, N.O.S., 3, III

### 15 Regulatory information

· *Safety, health and environmental regulations/legislation specific for the substance or mixture*· *Australian Inventory of Chemical Substances*

8052-41-3	Stoddard solvent
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy
64742-95-6	Solvent naphtha (petroleum), light arom.
95-63-6	1,2,4-trimethylbenzene
78-83-1	butanol
9003-29-6	Butene, homopolymer
25551-13-7	Trimethylbenzene
64742-47-8	Distillates (petroleum), hydrotreated light
98-82-8	cumene
112-62-9	methyl oleate
112-80-1	oleic acid, pure
64742-48-9	Naphtha (petroleum), hydrotreated heavy
103-65-1	propylbenzene
1330-20-7	xylene
108-67-8	mesitylene
526-73-8	1,2,3-trimethylbenzene
91-20-3	naphthalene
100-41-4	ethylbenzene

· *Standard for the Uniform Scheduling of Medicines and Poisons*

1330-20-7	xylene	S6
91-20-3	naphthalene	S6

· *GHS label elements* The product is classified and labelled according to the Globally Harmonised System (GHS).· *Hazard pictograms*· *Signal word* Danger· *Hazard-determining components of labelling:*

Stoddard solvent

1,2,4-trimethylbenzene

Naphtha (petroleum), hydrodesulfurized heavy

Solvent naphtha (petroleum), light arom.

· *Hazard statements*

Flammable liquid and vapour.

Causes serious eye damage.

May cause genetic defects.

(Contd. on page 9)



# Safety Data Sheet

## according to WHS Regulations

Printing date 10.03.2017

Version number 166

Revision: 10.03.2017

**Trade name: Sure Lift with Dye J6D**

(Contd. of page 8)

*May cause cancer.**Causes damage to the central nervous system through prolonged or repeated exposure.**May be fatal if swallowed and enters airways.***· Precautionary statements***If medical advice is needed, have product container or label at hand.**Keep out of reach of children.**Read label before use.**Keep away from heat/sparks/open flames/hot surfaces. No smoking.**IF SWALLOWED: Immediately call a POISON CENTER/ doctor.**IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.**IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.**Store locked up.**Dispose of contents/container in accordance with local/regional/national/international regulations.***· Directive 2012/18/EU****· Named dangerous substances - ANNEX I** None of the ingredients is listed.**· Seveso category P5c** FLAMMABLE LIQUIDS**· Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t**· Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t**· National regulations:****· Information about limitation of use:***Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.***· Technical instructions (air):**

Class	Share in %
NK	21.6

**· Waterhazard class:** Water hazard class 3 (Self-assessment): extremely hazardous for water.**· Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

*The provided information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.**This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.***· Department issuing SDS:** Environmental, Health & Safety Department**· Contact:** Environmental, Health & Safety Manager**· Abbreviations and acronyms:***ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)**IMDG: International Maritime Code for Dangerous Goods**IATA: International Air Transport Association**EINECS: European Inventory of Existing Commercial Chemical Substances**ELINCS: European List of Notified Chemical Substances**CAS: Chemical Abstracts Service (division of the American Chemical Society)**LC50: Lethal concentration, 50 percent**LD50: Lethal dose, 50 percent**PBT: Persistent, Bioaccumulative and Toxic**vPvB: very Persistent and very Bioaccumulative**Flam. Liq. 3: Flammable liquids – Category 3**Flam. Liq. 4: Flammable liquids – Category 4**Acute Tox. 4: Acute toxicity – Category 4**Skin Irrit. 2: Skin corrosion/irritation – Category 2*

(Contd. on page 10)

**Safety Data Sheet**  
**according to WHS Regulations**

Printing date 10.03.2017

Version number 166

Revision: 10.03.2017

**Trade name: Sure Lift with Dye J6D**

(Contd. of page 9)

*Eye Dam. 1: Serious eye damage/eye irritation – Category 1*  
*Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A*  
*Muta. 1A: Germ cell mutagenicity – Category 1A*  
*Muta. 1B: Germ cell mutagenicity – Category 1B*  
*Carc. 1A: Carcinogenicity – Category 1A*  
*Carc. 1B: Carcinogenicity – Category 1B*  
*Carc. 2: Carcinogenicity – Category 2*  
*Carc. 2: Carcinogenicity – Category 2*  
*STOT SE 3: Specific target organ toxicity (single exposure) – Category 3*  
*STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1*  
*Asp. Tox. 1: Aspiration hazard – Category 1*

AU